



# Lichtwellenleiter (LWL) Stecker und Kupplungen

Fibre optique (FO) connecteurs et raccords




LC APC



LC Uniboot PC




SC PC



LSH E2000 APC




ST PC




FC PC



CS PC



SN PC



MDC PC



MTP / MPO PC



Q-ODC (IP 68)



Lens Connector (IP 68)

PC=Physical Contact APC=Angled Physical Contact

CONNECTING THE DOTS













**CCM**  
CONNECTCOM

www.ccm.ch







## Farbcode LWL / Code couleur FO

|    | Swisscom<br>Code Swisscom  | DIN/VDE 0888<br>Code DIN   | TIA/EIA-598<br>TIA/EIA-598   | CCM Code<br>Code CCM |
|----|--|--|--|----------------------|
| 1  |  rot rouge        |  rot rouge        |  blau bleu        | RD                   |
| 2  |  grün vert        |  grün vert        |  orange orange    | GN                   |
| 3  |  gelb jaune       |  blau bleu        |  grün vert        | YE                   |
| 4  |  blau bleu        |  gelb jaune       |  braun brun       | BL                   |
| 5  |  weiss blanc      |  weiss blanc      |  grau gris        | WH                   |
| 6  |  violett violet   |  grau gris        |  weiss blanc      | VI                   |
| 7  |  orange orange    |  braun brun       |  rot rouge        | OR                   |
| 8  |  schwarz noir     |  violett violet   |  schwarz noir     | BK                   |
| 9  |  grau gris        |  türkis turquoise |  gelb jaune       | GY                   |
| 10 |  braun brun       |  schwarz noir     |  violett violet   | BN                   |
| 11 |  rosa rose        |  orange orange    |  rosa rose        | PK                   |
| 12 |  türkis turquoise |  rosa rose        |  türkis turquoise | TQ                   |

## Stecker und Kupplungen / Connecteurs et raccords

|          |                          |            | Farbcodierung<br>Stecker  | Farbcodierung<br>Kupplung   |
|----------|--------------------------|------------|---|---|
| SM-OS2   | 9/125 µm                 | (0° = PC)  |  |  |
| SM-OS2   | 9/125 µm                 | (8° = APC) |  |  |
| MM-OM1/2 | 62.5/125 µm<br>50/125 µm | (0° = PC)  |  |  |
| MM-OM3   | 50/125 µm                | (0° = PC)  |  |  |
| MM-OM4   | 50/125 µm                | (0° = PC)  |  |  |
| MM-OM5   | 50/125 µm                | (0° = PC)  |  |  |

## Patchkabel / Cordons de brassage

|          |   |             |
|----------|---|-------------|
| SM-OS1/2 |  | 9/125 µm    |
| MM-OM1   |  | 62.5/125 µm |
| MM-OM2   |  | 50/125 µm   |
| MM-OM3   |  | 50/125 µm   |
| MM-OM4   |  | 50/125 µm   |
| MM-OM5   |  | 50/125 µm   |